

Reliability Report 1SP0335V2

Scope

The goal of this document is to explain reliability tests done on 1SP0335V2 family. Following drivers are covered by this family:

1SP0335V2M1-FZ800R33KL2C_B5	1SP0335V2M1-5SNA0750G650300	1SP0335V2M1-5SNA0800J450300
1SP0335V2M1-FZ1200R33KL2C_B5	1SP0335V2M1-FZ500R65KE3	1SP0335V2M1-MBN1200H45E2-H
1SP0335V2M1-CM900HG-90H	1SP0335V2M1-FZ600R65KE3	1SP0335V2M1-MBN750H65E2
1SP0335V2M1-5SNA0650J450300	1SP0335V2M1-CM750HG-130R	1SP0335V2M1-CM400HG-130H
1SP0335V2M1-DIM1200ASM45-TS001	1SP0335V2M1-5SNA0500J650300	1SP0335V2M1-33
1SP0335V2M1ENG-DIM1200ASM45-TS001	1SP0335V2M1-CM1200HG-90R	1SP0335V2M1-45
1SP0335V2M1-CM1000HG-130XA	1SP0335V2M1-FZ1200R45KL3_B5	1SP0335V2M1-65
1SP0335V2M1-5SNA1200G450300	1SP0335V2M1-FZ250R65KE3	1SP0335V2M1-MBN500H65E2
1SP0335V2M1-FZ400R65KF2	1SP0335V2M1-CM600HG-90H	
1SP0335V2M1-FZ750R65KE3	1SP0335V2M1-5SNA0600G650100	

Serial Environmental Load

Serial stress: all the tests in the table below are done on the same samples

Test Name	Test Settings	Results
Vibration	IEC 60068-2-6:2007-12: Frequency range: 5Hz to 200Hz	Pass
(sinusoidal)	Cross-over frequency: 8.4Hz	
	Displacement amplitude below cross-over frequency: ±3.5mm	
	Acceleration amplitude above cross-over frequency: 1g	
	Sweep rate: 1.0 Okt/min	
	Test duration per axis: 20 sweeps (X, Y and Z)	
	DUT not powered	
Shock	IEC 60068-2-27:2008-02: Pulse shape: Half-sine	Pass
	Peak acceleration: 15g	
	Corresponding duration of the nominal pulse: 6ms	
	Number of shocks in each of the six directions: 100	
	Axis: X, Y and Z (pos. and neg.)	
	DUT not powered	
Cold	IEC 60068-2-1:2007-03: Test: Ae	Pass
	Temperature: -40°C	
	Duration: 96h	
	DUT powered	
Dry heat	IEC 60068-2-2:2007-07: Test:Be	Pass
	Temperature: 85°C	
	Duration: 96h	
	DUT powered	
Change of	IEC 60068-2-14:2009-01: Test: Nb	Pass
temperature	Cycles: 2	
	Start temperature: 20°C	
	Low temperature: -40°C	
	High temperature: 85°C	
	Rate of change: 10K/min	
	Exposure time at lower/upper temperature: 30min	



	DUT powered	
Damp heat	IEC 60068-2-78:2012-10: Temperature: 40°C Relative humidity: 93% Duration of test: 96h DUT not powered	Pass